

**AAMA/WDMA/CSA
101/I.S.2/A440-08**



NAFS
North American Fenestration
Standard/Specification for
windows, doors, and skylights



Contents

Preface *vii*

0 Introduction 1

- 0.1 General 1
- 0.1.1 Applicability 1
- 0.1.2 Content 1
- 0.2 Performance classes and levels 2
- 0.2.1 Performance classes 2
- 0.2.2 Guidance for the specifier/purchaser 2
- 0.2.3 Performance grade (PG) designations 2
- 0.2.4 Side-hinged door systems 3
- 0.2.5 Positive and negative design pressure (DP) 3
- 0.2.6 Water penetration resistance testing and performance 4
- 0.2.7 Operation/cycling performance 5
- 0.3 Short-form specification 6

1 Scope 6

- 1.1 General 6
- 1.2 Terminology 7
- 1.3 Units of measurement 7

2 Reference publications 8

3 Definitions 18

4 General requirements 28

- 4.1 General 28
- 4.2 Gateway performance requirements 28
- 4.2.1 General 28
- 4.2.2 Alternative minimum test sizes for Performance Class R products (optional) 28
- 4.3 Performance grades (PG) 29
- 4.3.1 Assignment of performance grade (PG) 29
- 4.3.2 Optional performance grades (PG) 29
- 4.4 Product designations 29
- 4.4.1 General 29
- 4.4.2 Primary designator 32
- 4.4.3 Secondary designator 41
- 4.5 Dual windows or dual doors 44
- 4.5.1 General 44
- 4.5.2 Requirements 45

5 Testing 46

- 5.1 Testing sequence 46
- 5.2 Test specimen requirements 46
- 5.2.1 General 46
- 5.2.2 Composite units and combination assemblies 46
- 5.2.3 Alterations 46
- 5.2.4 Specimen size 47
- 5.2.5 Test specimen installation 47
- 5.3 Testing methods 50
- 5.3.1 Operating force and force to latch 50

- 5.3.2 Air leakage resistance test 54
- 5.3.3 Water penetration resistance test 55
- 5.3.4 Uniform load tests 56
- 5.3.5 Forced-entry resistance test 58
- 5.3.6 Auxiliary (durability) tests 58
- 5.3.7 Condensation resistance (optional) 74
- 5.3.8 Thermal transmittance (optional) 74
- 5.3.9 Acoustical performance (optional) 75
- 5.3.10 Impact performance (optional) 75
- 5.4 Laboratory test report 75

6 Materials 77

- 6.1 Material tolerance 77
- 6.2 Glazing and glass 77
 - 6.2.1 Reference standards 77
 - 6.2.2 General requirements 77
 - 6.2.3 Glazing selection 77
 - 6.2.4 Removable multiple glazing panels 81
 - 6.2.5 Plastic glazing 81
- 6.3 Framing/cladding materials 83
 - 6.3.1 General 83
 - 6.3.2 Wood 83
 - 6.3.3 Wood flush and molded fiber doors 83
 - 6.3.4 Vinyl 84
 - 6.3.5 Cellular PVC 84
 - 6.3.6 Aluminum 85
 - 6.3.7 Fiberglass 85
 - 6.3.8 Steel 86
 - 6.3.9 Cellulosic composite materials 86
 - 6.3.10 Fiber-reinforced PVC 86
 - 6.3.11 Acrylonitrile-butadiene-styrene (ABS) 87
 - 6.3.12 Doorlite insert frame materials 87
 - 6.3.13 Other materials 87

7 Components 88

- 7.1 Hardware 88
 - 7.1.1 General 88
 - 7.1.2 Hung window hardware 88
 - 7.1.3 Casement, awning, hopper, and projected window hardware 88
 - 7.1.4 Door hardware 88
 - 7.1.5 Hinged window hardware 89
 - 7.1.6 Tropical window hardware 89
 - 7.1.7 Dual-action window hardware 90
- 7.2 Fasteners 90
- 7.3 Reinforcing 91
- 7.4 Weatherstrip 91
- 7.5 Insect screens 91
- 7.6 Sealants 92
- 7.7 Coatings/finishes 92
- 7.8 Mullions 92
 - 7.8.1 Mullion rating 92
 - 7.8.2 Composite units 97
 - 7.8.3 Combination assemblies 98
 - 7.8.4 Field mulling without manufacturer's involvement 98

- 7.8.5 Windload deflection 98
- 7.8.6 Operational interference 99
- 7.8.7 Vertical (dead load) deflection 99
- 7.9 Integral ventilating systems/devices 99
- 7.10 Blinds in dual-glazed products 99
- 7.11 Setting blocks 99
- 7.12 Dividers (muntins) 100
 - 7.12.1 True divided lites 100
 - 7.12.2 Simulated divided lites, removable grids, and grills 100

8 Fenestration type and test size 101

- 8.1 General 101
- 8.2 Product dimensions and tolerances 101
 - 8.2.1 Dimensions 101
 - 8.2.2 Tolerances 103
- 8.3 Qualification of designs, configurations, and assemblies 103
 - 8.3.1 General 103
 - 8.3.2 Geometry and components 103
 - 8.3.3 Operation and orientation 104
 - 8.3.4 Composite units and unique framing members 104
- 8.4 Specialty products, basement windows, hinged windows, side lites, and transoms 108
 - 8.4.1 Specialty products 108
 - 8.4.2 Basement windows 108
 - 8.4.3 Hinged windows 109
 - 8.4.4 Side lites and transoms 109

9 Alternative minimum test sizes and minimum performance grades (PG) for selected Class R products (optional) 110

Annexes

- A** (informative) — Contact information for standards development organizations 118

Tables

- 1** — Gateway requirements 28
- 2** — U.S. (only) optional performance grades (PG) 30
- 3** — Canada (only) optional performance grades (PG) 31
- 4** — Optional performance grades (PG) for unit skylights, TDDs, and roof windows 32
- 5** — Product types 36
- 6** — Canadian (only) operating force requirements 51
- 7** — U.S. (only) operating force requirements 52
- 8** — Maximum allowable air leakage 54
- 9** — Canadian (only) air infiltration/exfiltration levels 54
- 10** — Deflection limits for sash/leaf torsion test 61
- 11** — Deflection limits for sash vertical deflection test 62
- 12** — Deflection limits for sash/leaf concentrated load test on latch rail 65
- 13** — Deflection limits for vertical concentrated load test 66
- 14** — Deflection limit for vertical concentrated load test on intermediate frame rails 67
- 15** — Loads for distributed load test 68
- 16** — Loads for stabilizing arm load test 69
- 17** — Load for hold-open arm/stay bar test 70
- 18** — Deflection limits for sash blocked operation test 71
- 19** — Operation/cycling performance (side-hinged door systems) 74
- 20** — Allowable IGU glass loads for Examples 1 and 2 in Clause 6.2.3.3 79
- 21** — Plastic glazing combustibility classes 83

- 22** — Door hardware reference Standards 89
 - 23** — Requirements for fasteners and reinforcing 91
 - 24** — Requirements for exterior finishes 92
 - 25** — Window assembly qualification 107
 - 26** — Alternative minimum test sizes and associated minimum performance grades (PG) for selected Class R products 110
 - 27** — Gateway performance requirements 111
-

Figures

- 1** — Short-form specification 6
- 2** — Primary designator (Example 1) 33
- 3** — Primary designator (Example 2) 34
- 4** — Primary designator (Example 3) 35
- 5** — Product type illustrations 37
- 6** — Examples of specialty products 40
- 7** — Secondary designator (Example 1) 43
- 8** — Secondary designator (Example 2) 44
- 9** — Secondary designator (Example 3) 44
- 10** — Corner sealant detail 47
- 11** — Test specimen mounting 48
- 12** — Set-up for thermoplastic corner weld test 59
- 13** — Set-up for sash/leaf torsion test 60
- 14** — Set-up for sash vertical deflection test 62
- 15** — Perpendicular load for sash/leaf concentrated load test on latch rail 63
- 16** — Parallel load for sash/leaf concentrated load test on latch rail 64
- 17** — Set-up for vertical concentrated load test 66
- 18** — Set-up for vertical concentrated load test on intermediate frame rails 67
- 19** — Set-up for distributed load test 68
- 20** — Set-up for stabilizing arm load test 69
- 21** — Set-up for hold-open arm/stay bar test 70
- 22** — Set-up for awning, hopper, projected hardware load test 71
- 23** — Set-up for unit dead load test 73
- 24** — Test report summary of results 76
- 25** — Mullion types and applications 94
- 26** — Product dimension measurement 102
- 27** — Window assembly qualification — Typical configurations 105
- 28** — Side-hinged door assembly qualification 107